



OKAM K01-2220



Universal Server

2U DP 24+2-Bay NVMe / SATA / SAS-4



Key Features

- Dual Intel® Xeon® 6700/6500 Series processors
- 32 x DIMMs, 8-channel DDR5 RDIMM
- 24 x 2.5" Gen5 NVMe / SATA / SAS-4 hot-swap bays
- 2 x 2.5" Gen5 NVMe / SATA / SAS-4 hot-swap on the rear
- 2 x M.2 slot with PCIe Gen5 x4 interface
- 2 x FHFL PCIe Gen5 x16 slots
- 2 x FHFL PCIe Gen5 x8 slots
- 2 x FHHL PCIe Gen5 x8 slots
- 1 x HHHL PCIe Gen5 x8 slot
- 1 x OCP 3.0 Gen5 x16 slot
- 1 x OCP 3.0 PCIe Gen5 x8 slot
- 1+1 2000W 80 PLUS Titanium redundant power supplies

Virtualization

VDI

HCI

Large databases

Storage-intensive applications

Specifications

Dimensions 2U (W438 x H87 x D770 mm)

CPU Intel® Xeon® 6 processors:

- Intel® Xeon® 6700E Series processors
- Intel® Xeon® 6700P Series processors
- Intel® Xeon® 6500P Series processors

Dual processors, TDP up to 350W

OS compatibility Visit our website for a list of compatible operating systems

Chipset System on Chip

Memory 32 x DIMMs, 8-channel DDR5 RDIMM
Up to 6400 MT/s (1DPC), 5200 MT/s (2DPC)
*MRDIMMs are only supported with Intel®Xeon® 6 processors with P-cores and in a 1DPC configuration

LAN 1/2/4 Ports OCP 3.0 LAN support
1 x 10/100/1000 Mbps Management LAN

Video ASPEED® AST2600:

- 1 x Mini DisplayPort

Storage

Front hot-swap:
24 x 2.5" Gen5 NVMe / SATA / SAS-4*

Rear hot-swap:
2 x 2.5" NVMe / SATA / SAS-4*

Internal M.2:
2 x M.2 (2280/22110), PCIe Gen5 x4

*Storage card is required to support SATA and SAS drives.
SAS card is required to support SAS drives.

RAID Requires RAID add-in cards
Onboard VROC key header

PCIe expansion slots

- 2 x FHFL PCIe Gen5 x16 slots
- 2 x FHFL PCIe Gen5 x8 slots
- 2 x FHHL PCIe Gen5 x8 slots
- 1 x HHHL PCIe Gen5 x8 slot
- 1 x OCP 3.0 Gen5 x16 slot
- 1 x OCP 3.0 PCIe Gen5 x8 slot

I/O ports

Front:
2 x USB 3.2 Gen1

Rear:
2 x USB 3.2 Gen1, 1 x Mini DisplayPort, 2 x RJ45, 1 x MLAN

Backplane board

Front: PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
Rear: PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s

Security modules TPM 2.0

Power supply 1+1 2000W 80 PLUS Titanium redundant power supplies
AC Input: 100-240V

System management ASPEED® AST2600 Baseboard Management Controller
KERNO Management Console (AMI MegaRAC SP-X)

System fans 6 x 60x60x56 mm

Operating properties Operating: 10°C to 30°C, 8% to 80% (non-condensing)
Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)

Packaging content 1 x 2U chassis
1 x Mini DisplayPort to D-Sub cable
1 x 2-section rail kit

Warranty 3- to 5-year limited warranty

Learn more at www.kerno.ae. All specifications are subject to change without notice. Please visit our website for the latest information.

Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.

All other brands, logos and names are the property of their respective owners.



OKAM K01-2220



Universal Server

2U DP 12+2-Bay SATA / SAS-4 + 2 x PCIe Gen5 GPUs

Key Features

- Supports up to 2 x dual-slot Gen5 GPUs
- Dual Intel® Xeon® 6700/6500 Series processors
- 32 x DIMMs, 8-channel DDR5 RDIMM
- 12 x 3.5"/2.5" Gen5 NVMe / SATA / SAS-4 hot-swap bays
- 2 x 2.5" SATA / SAS-4 hot-swap on the rear
- 2 x M.2 slot with PCIe Gen5 x4 interface
- 2 x FHFL PCIe Gen5 x16 slots for GPUs
- 2 x FHHL PCIe Gen5 x16 slot
- 1 x HHHL PCIe Gen5 x8 slot
- 1 x OCP 3.0 PCIe Gen5 x16 slot support NCSI
- 1 x OCP 3.0 PCIe Gen5 x8 slot
- Dual 2000W 80 PLUS Titanium redundant power supply

Virtualization

VDI

HCI

Large databases

Storage-intensive applications



Specifications

Dimensions 2U (W438 x H87 x D770 mm)

CPU Intel® Xeon® 6 processors:

- Intel® Xeon® 6700E Series processors
- Intel® Xeon® 6700P Series processors
- Intel® Xeon® 6500P Series processors

 Dual processors, TDP up to 350W

OS compatibility Visit our website for a list of compatible operating systems

Chipset System on Chip

Memory 32 x DIMMs, 8-channel DDR5 RDIMM
 Up to 6400 MT/s (1DPC), 5200 MT/s (2DPC)

LAN 1 x 10/100/1000 Mbps Management LAN
 Support for 1/2/4 Port OCP NICs

Video ASPEED® AST2600:

- 1 x Mini DisplayPort

Storage
Front hot-swap:
 12 x 3.5"/2.5" Gen5 NVMe / SATA / SAS-4*
Rear hot-swap:
 2 x 2.5" SATA / SAS-4*
Internal M.2:
 2 x M.2 (2280), PCIe Gen5 x4
 *Storage card is required to support SATA and SAS drives.

RAID Requires RAID add-in cards
 Onboard VROC key header

PCIe expansion slots
 2 x FHFL PCIe Gen5 x16 slots for GPUs
 2 x FHHL PCIe Gen5 x16 slots
 1 x HHHL PCIe Gen5 x8 slot
 1 x OCP 3.0 PCIe Gen5 x16 slot support NCSI
 1 x OCP 3.0 PCIe Gen5 x8 slot

I/O ports
Front:
 1 x USB 3.2 Gen1, 1 x USB 2.0
Rear:
 2 x USB 3.2 Gen1, 1 x Mini DisplayPort, 1 x MLAN

Backplane board
Front: PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
Rear: PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s

Security modules TPM 2.0

Power supply Dual 2000W 80 PLUS Titanium redundant power supply
 AC Input: 100-240V

System management ASPEED® AST2600 Baseboard Management Controller
 KERNO Management Console (AMI MegaRAC SP-X)

System fans 6 x 60x60x56 mm

Operating properties
 Operating: 10°C to 30°C, 8% to 80% (non-condensing)
 Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)

Packaging content
 1 x 2U chassis
 1 x Mini DisplayPort to D-Sub cable
 1 x 2-section rail kit

Warranty 3- to 5-year limited warranty

Learn more at www.kerno.ae. All specifications are subject to change without notice. Please visit our website for the latest information.

Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.

All other brands, logos and names are the property of their respective owners.