



OKAM K01-22A0



Universal Server

2U DP 24+2-Bay Gen5 NVMe / SATA / SAS-4



Key Features

- Dual AMD EPYC™ 9005 Series processors
- 24 x DIMMs, 12-channel DDR5 RDIMM
- 24 x 2.5" Gen5 NVMe / SATA / SAS-4 hot-swap bays
- 2 x 2.5" Gen5 NVMe / SATA / SAS-4 hot-swap on the rear
- 2 x FHFL PCIe Gen5 x16 slots
- 2 x FHFL PCIe Gen5 x8 slots
- 2 x FHHL PCIe Gen5 x8 slots
- 1 x HHHL PCIe Gen5 x8 slot
- 1 x OCP 3.0 PCIe Gen5 x16 slot
- 1 x OCP NIC 3.0 PCIe Gen5 x8 slot
- 1+1 2000W 80 PLUS Titanium redundant power supplies

Storage-intensive applications

Large databases

HPC

Specifications

Dimensions 2U (W438 x H87 x D770 mm)

CPU AMD EPYC™ 9005 Series processors
Dual processor, cTDP up to 400W
• The EPYC 9005 series processors with a TDP of 400W are supported only under ambient temperatures of 25°C

OS compatibility Visit our website for a list of compatible operating systems

Socket 2 x LGA 6096 (Socket SP5)

Chipset System on Chip

Memory 24 x DIMMs, 12-channel DDR5 RDIMM
Up to 6400 MT/s

LAN 1 x 10/100/1000 Mbps Management LAN
1/2/4 Port OCP NIC support

Video Integrated in ASPEED® AST2600:
• 1 x Mini DisplayPort

Storage **Front hot-swap:**
24 x 2.5" Gen5 NVMe / SATA / SAS-4*
Rear hot-swap:
2 x 2.5" Gen5 NVMe / SATA / SAS-4*

*SAS card is required to support SAS drives

RAID Requires RAID add-in cards

Backplane board **Front:** PCIe Gen5 or SATA6Gb/s or SAS-4 24Gb/s
Rear: PCIe Gen5 or SATA6Gb/s or SAS-4 24Gb/s

PCIe expansion slots 2 x FHFL PCIe Gen5 x16 slots
2 x FHFL PCIe Gen5 x8 slots
2 x FHHL PCIe Gen5 x8 slots
1 x HHHL PCIe Gen5 x8 slot
1 x OCP 3.0 PCIe Gen5 x16 slot
1 x OCP NIC 3.0 PCIe Gen5 x8 slot

I/O ports **Front:**
1 x USB 3.2 Gen1, 1 x USB 2.0
Rear:
2 x USB 3.2 Gen1, 1 x Mini DisplayPort, 1 x MLAN

Security modules TPM 2.0

Power supply 1+1 2000W 80 PLUS Titanium redundant power supplies
AC Input: 100-240V

System management ASPEED® AST2600 Baseboard Management Controller
KERNO Management Console web interface

System fans 6 x 60x60x56 mm

Operating properties Operating: 10°C to 30°C, 8% to 80% (non-condensing)
Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)

Packaging content 1 x 2U chassis
1 x Mini DisplayPort to D-Sub cable
1 x 2-section rail kit

Warranty 3- to 5-year limited warranty

Learn more at www.kerno.ae. All specifications are subject to change without notice. Please visit our website for the latest information.

AMD, the AMD Arrow logo, EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.

All other brands, logos and names are the property of their respective owners.



OKAM K01-22A0



Universal Server

2U DP 12+2-Bay Gen5 NVMe / SATA / SAS-4 + 2 x PCIe Gen5 GPUs

Key Features

- Supports up to 2 x dual-slot Gen5 GPUs
- Dual AMD EPYC™ 9005 Series processors
- 24 x DIMMs, 12-channel DDR5 RDIMM
- 12 x 3.5"/2.5" Gen5 NVMe / SATA / SAS-4 hot-swap bays
- 2 x 2.5" Gen5 NVMe / SATA / SAS-4 hot-swap on the rear
- 2 x FHFL PCIe Gen5 x16 slots for GPUs
- 2 x FHHL PCIe Gen5 x16 slots
- 1 x HHHL PCIe Gen5 x8 slot
- 1 x OCP 3.0 PCIe Gen5 x16 slot
- 1 x OCP NIC 3.0 PCIe Gen5 x8 slot
- 1+1 2000W 80 PLUS Titanium redundant power supplies

Storage-intensive applications

Large databases

HPC



Specifications

Dimensions 2U (W438 x H87 x D770 mm)

CPU AMD EPYC™ 9005 Series processors
Dual processor, cTDP up to 400W:

- The EPYC 9005 series processors with a TDP of 400W are supported only under ambient temperatures of 25°C

OS compatibility Visit our website for a list of compatible operating systems

Socket 2 x LGA 6096 (Socket SP5)

Chipset System on Chip

Memory 24 x DIMMs, 12-channel DDR5 RDIMM
Up to 6400 MT/s

LAN 1 x 10/100/1000 Mbps Management LAN
1/2/4 Port OCP NIC support

Video Integrated in ASPEED® AST2600:

- 1 x Mini DisplayPort

Storage **Front hot-swap:**
12 x 3.5"/2.5" Gen5 NVMe / SATA / SAS-4*
Rear hot-swap:
2 x 2.5" Gen5 NVMe / SATA / SAS-4*
*SAS card is required to support SAS drives

RAID Requires RAID add-in cards

Backplane board **Front:** PCIe Gen5 or SATA6Gb/s or SAS-4 24Gb/s
Rear: PCIe Gen5 or SATA6Gb/s or SAS-4 24Gb/s

PCIe expansion slots 2 x FHFL PCIe Gen5 x16 slots for GPU
2 x FHHL PCIe Gen5 x16 slots
1 x HHHL PCIe Gen5 x8 slot
1 x OCP 3.0 PCIe Gen5 x16 slot
1 x OCP NIC 3.0 PCIe Gen5 x8 slot

I/O ports **Front:**
1 x USB 3.2 Gen1, 1 x USB 2.0
Rear:
2 x USB 3.2 Gen1, 1 x Mini DisplayPort, 1 x MLAN

Security modules TPM 2.0

Power supply 1+1 2000W 80 PLUS Titanium redundant power supplies
AC Input: 100-240V

System management ASPEED® AST2600 Baseboard Management Controller
KERNO Management Console web interface

System fans 6 x 60x60x56 mm

Operating properties Operating: 10°C to 30°C, 8% to 80% (non-condensing)
Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)

Packaging content 1 x 2U chassis
1 x Mini DisplayPort to D-Sub cable
1 x 2-section rail kit

Warranty 3- to 5-year limited warranty

Learn more at www.kerno.ae. All specifications are subject to change without notice. Please visit our website for the latest information.

AMD, the AMD Arrow logo, EPYC and combinations thereof are trademarks of Advanced Micro Devices, Inc.

All other brands, logos and names are the property of their respective owners.